TECHNICAL SPECIFICATIONS

KTM 125 DUKE

ENGINE

Design	1-CYLINDER, 4-STROKE ENGINE
Displacement	124.71 CM³
Torque	12 NM
Transmission	6-SPEED
Cooling	LIQUID COOLED
EMS	BOSCH EMS
Engine oil	MOTOREX FORMULA 4T
Drive type	COMBUSTION

CHASSIS

Front suspension	**WP-USD, AER 43, Ø 43 MM**
Rear suspension	**WP MONOSHOCK**
Front brake disc diameter	**300 MM**
Rear brake disc diameter	**230 MM**
Front brake	**FOUR-PISTON RADIAL FIXED CALLIPER, BRAKE DISC**
Rear brake	**SINGLE-PISTON FLOATING CALLIPER, BRAKE DISC**
Chain	**520 X-RING**
Frame design	**STEEL TRELLIS FRAME, POWDER COATED**
Silencer	**STAINLESS STEEL PRIMARY AND ALUMINIUM SECONDARY SILENCER**
Steering head angle	**65 °**
Rear subframe design	**STEEL TRELLIS FRAME, POWDER COATED**
Wheelbase	**1367 MM**

DIMENSIONS

Seat height	**822 MM**
Tank capacity (approx.)	**11 L**
Ground clearance	**155 MM**
Wheelbase tolerance	**15 MM**
Front wheel diameter	**17 "**
Rear wheel diameter	**17 "**
Front wheel width	**3 "**
Rear wheel width	**4 "**
Wheels	**CAST ALUMINIUM WHEELS**